

Over Voltage & Under Voltage Cut-Off with Safe Restore™



Model: OVCD-277-DR



Model: OVCD-230-DR

Features

- Dinrail Mount
- Extends The Life Of Your Fixture By Eliminating Temporary Over/Under Voltages that Can Harm Sensitive Electronic Components
- Safe Restore™
 - Instant Drop on Over/Under Voltage Condition
 - When Voltage Returns to Normal, Unit Auto Resets
- Automatically Shuts Off Power to the Fixture When Nominal Voltage Decreases by 40V
- Automatically Shuts Off Power to the Fixture When Nominal Voltage Increases by 40V
- For Volume Purchases, We Can Adjust Voltage Settings

SPECIFICATIONS	Product Model OVCD-277-DR	Product Model OVCD-230-DR
Green LED ON** Denotes Input Power ON	✓	✓
Red LED light ON** Denotes Over/Under Voltage Condition	✓	✓
Over-Voltage Value	AC317V±5V	AC270V±5V
Under-Voltage Value	AC237V±5V	AC190V±5V
Reset Time	180 Seconds	60 Seconds
Power-On Delay	90 Seconds	90 Seconds
IP Rating	10	10
Wire Connecting	18-16 AWG Multi-Strand Soft Wire	18-16 AWG Multi-Strand Soft Wire
Altitude	<2000m	<2000m
Environment Temperature	-40°C to +85°C	-40°C to +85°C
Rated Frequency	50-60Hz	50-60Hz
Working Current	5A	40A
Working Voltage	VAC 277	VAC 230
Weight	158 g / 5.5 oz (approx.)	136 g / 4.8 oz (approx.)